

EG1 液压齿轮泵
EG1 Hydraulic Gear Pumps


型号说明 Model Code

①	EG1	CODE													
②	A	FLANGE AND COVER	A	Aluminium											
③	09	DISPLACEMENT	09	13	16	21	25	31	38	43	50	62	78	99	
			0.95	1.26	1.64	2.05	2.56	3.15	3.80	4.28	4.97	6.21	7.80	9.85	
④	ST0	FLANGE	ST0	S20		MZI			MZD&MZS			EZ1			
⑤	T80	SHAFT	T80	P30 S90		T50 F50 D60			T50 F50 D60			E50			
⑥	EE4	CONNECTION	EEEx	TT4	GG4	UUx									
⑦	D	ROTATION	D	Clockwise rotation											
			S	Anticlockwise rotation											
⑧	0	STANDARD COVER	0	Standard											
⑨	0	SEALS	0	Nbr seals											
			V	Viton® seals											

性能参数 Specification

Size	Displacement (in ³ /rev)	Max speed rpm	Max flow (gpm)	Min speed rpm	Min flow (gpm)	Min Volum. Effic.* %
EG1-09	0.95 (0.058)	6000	5.7 (1.50)	600	0.5 (0.14)	90
EG1-13	1.26 (0.077)	6000	7.5 (1.99)	600	0.7 (0.18)	92
EG1-16	1.64 (0.100)	6000	9.8 (2.60)	400	0.6 (0.16)	95
EG1-21	2.05 (0.125)	5500	11.3 (2.98)	400	0.8 (0.21)	95
EG1-25	2.56 (0.156)	5500	14.1 (3.72)	400	1 (0.26)	95
EG1-31	3.15 (0.192)	4500	14.2 (3.75)	400	1.2 (0.32)	95
EG1-38	3.80 (0.232)	4000	15.2 (4.01)	400	1.4 (0.38)	95
EG1-43	4.28 (0.261)	3500	15 (3.96)	400	1.6 (0.43)	95
EG1-50	4.97 (0.303)	3000	14.9 (3.94)	400	1.9 (0.50)	95
EG1-62	6.21 (0.379)	2700	16.8 (4.43)	400	2.4 (0.62)	95
EG1-78	7.80 (0.476)	2500	19.5 (5.15)	400	3.0 (0.78)	95
EG1-99	9.85 (0.601)	2000	19.7 (5.20)	400	3.7 (0.99)	95

* Volumetric efficiency at 1500 rpm



ST0
Standard flange



MZD / MZS
Ø32 flange with delivery hole



MZI
Ø32 flange for power pack



S20
Sae AA flange




EZ1
E32C for electro pump

EG1 液压齿轮泵


EG1 Hydraulic Gear Pumps

Standard Flange ST0



Size		EG1-09	EG1-13	EG1-16	EG1-21	EG1-25	EG1-31	EG1-38	EG1-43	EG1-50	EG1-62	EG1-78	EG1-99
Dimension	A	35	35.6	36.4	37.2	38.2	39.3	40.6	41.5	42.9	45.3	48.4	52.4
	mm(in)	(1.38)	(1.40)	(1.43)	(1.46)	(1.50)	(1.55)	(1.60)	(1.63)	(1.69)	(1.78)	(1.91)	(2.06)
Dimension	B	74.4	75.2	76.7	78.3	80.3	82.6	85.1	87	90.1	94.9	100.7	109.1
	mm(in)	(2.93)	(2.96)	(3.02)	(3.08)	(3.16)	(3.25)	(3.35)	(3.43)	(3.55)	(3.74)	(3.96)	(4.30)
Weight(kg)		0.887	0.893	0.909	0.93	0.964	0.992	1.033	1.055	1.108	1.177	1.251	1.379

SAE AA Flange S20




Size		EG1-09	EG1-13	EG1-16	EG1-21	EG1-25	EG1-31	EG1-38	EG1-43	EG1-50	EG1-62	EG1-78	EG1-99
Dimension	A	38.5	39.1	39.9	40.7	41.7	42.8	44.1	45.0	46.4	48.8	51.9	55.9
	mm(in)	(1.516)	(1.539)	(1.569)	(1.600)	(1.640)	(1.685)	(1.734)	(1.772)	(1.825)	(1.919)	(2.041)	(2.199)
Dimension	B	77.9	78.7	80.2	81.8	83.8	86.1	88.6	90.5	93.6	98.4	104.2	112.6
	mm(in)	(3.065)	(3.098)	(3.157)	(3.220)	(3.299)	(3.390)	(3.488)	(3.563)	(3.683)	(3.872)	(4.102)	(4.431)
Weight(kg)		0.912	0.915	1.012	0.945	0.981	1.008	1.05	1.081	1.124	1.193	1.28	1.396

EG1 液压齿轮泵


EG1 Hydraulic Gear Pumps

ø32 Flange For Power Pack MZI



Size	EG1-09	EG1-13	EG1-16	EG1-21	EG1-25	EG1-31	EG1-38	EG1-43	EG1-50	EG1-62	EG1-78	EG1-99
Dimension	A	35	35.6	36.4	37.2	38.2	39.3	40.6	41.5	42.9	45.3	52.4
	mm(in)	(1.38)	(1.40)	(1.43)	(1.46)	(1.50)	(1.55)	(1.60)	(1.63)	(1.69)	(1.78)	(2.06)
	B	74.4	75.2	76.7	78.3	80.3	82.6	85.1	87	90.1	94.9	109.1
	mm(in)	(2.93)	(2.96)	(3.02)	(3.08)	(3.16)	(3.25)	(3.35)	(3.43)	(3.55)	(3.74)	(4.30)
	L	62.8	64	65.5	67.1	69.1	71.4	73.9	75.8	78.5	83.3	97.5
	mm(in)	(2.47)	(2.52)	(2.58)	(2.64)	(2.72)	(2.81)	(2.91)	(2.98)	(3.09)	(3.28)	(3.84)
Weight(kg)	0.781	0.806	0.823	0.844	0.875	0.903	0.94	0.963	1.007	1.072	1.147	1.266

ø32 Flange With Delivery Hole MZD/MZS




Size	EG1-09	EG1-13	EG1-16	EG1-21	EG1-25	EG1-31	EG1-38	EG1-43	EG1-50	EG1-62	EG1-78	EG1-99
Dimension	A	35	35.6	36.4	37.2	38.2	39.3	40.6	41.5	42.9	45.3	52.4
	mm(in)	(1.38)	(1.40)	(1.43)	(1.46)	(1.50)	(1.55)	(1.60)	(1.63)	(1.69)	(1.78)	(2.06)
	B	74.4	75.2	76.7	78.3	80.3	82.6	85.1	87	90.1	94.9	109.1
	mm(in)	(2.93)	(2.96)	(3.02)	(3.08)	(3.16)	(3.25)	(3.35)	(3.43)	(3.55)	(3.74)	(4.30)
C	73.5	74.7	76.2	77.8	79.8	82.1	84.6	86.5	89.2	94	100.2	108.2
	mm(in)	(2.89)	(2.94)	(3.00)	(3.06)	(3.14)	(3.23)	(3.33)	(3.51)	(3.70)	(3.94)	(4.26)
L	62.8	64	65.5	67.1	69.1	71.4	73.9	75.8	78.5	83.3	89.5	97.5
	mm(in)	(2.47)	(2.52)	(2.58)	(2.64)	(2.72)	(2.81)	(2.91)	(2.98)	(3.09)	(3.52)	(3.84)
Weight(kg)	0.781	0.806	0.823	0.844	0.875	0.903	0.94	0.963	1.007	1.072	1.147	1.266

EG1 液压齿轮泵

EG1 Hydraulic Gear Pumps

Flange E32C For Electro Pump EZ1



Size		EG1-09	EG1-13	EG1-16	EG1-21	EG1-25	EG1-31	EG1-38	EG1-43	EG1-50	EG1-62	EG1-78	EG1-99
Dimension	A	35	35.6	36.4	37.2	38.2	39.3	40.6	41.5	42.9	45.3	48.4	52.4
	mm(in)	(1.38)	(1.40)	(1.43)	(1.46)	(1.50)	(1.55)	(1.60)	(1.63)	(1.69)	(1.78)	(1.91)	(2.06)
	B	74.4	75.2	76.7	78.3	80.3	82.6	85.1	87	90.1	94.9	100.7	109.1
	mm(in)	(2.93)	(2.96)	(3.02)	(3.08)	(3.16)	(3.25)	(3.35)	(3.43)	(3.55)	(3.74)	(3.96)	(4.30)
	L	62.8	64	65.5	67.1	69.1	71.4	73.9	75.8	78.5	83.3	89.5	97.5
	mm(in)	(2.47)	(2.52)	(2.58)	(2.64)	(2.72)	(2.81)	(2.91)	(2.98)	(3.09)	(3.28)	(3.52)	(3.84)
Weight(kg)		0.784	0.771	0.789	0.809	0.84	0.867	0.904	0.927	0.971	1.035	1.113	1.227



Connections

STANDARD COVER

Size	Code
09-99	0

SUCTION ON THE COVER BSP THREADED

Size	Code
09-99	1




EG1 液压齿轮泵

EG1 Hydraulic Gear Pumps


Shafts

T80




TAPER 1:8
Max torque 28 Nm

T50




TAPER 1:5
Max torque 33 Nm

D60




DIN Z6
Max torque 26 Nm

F50




TANG DRIVE FOR POWER PACK
Max torque 20 Nm

E50




TANG DRIVE ELECTRIC PUMP
Max torque 20 Nm

P30



SAE CYLINDRICAL
Max torque 33 Nm

S90



SAE SPLINED 9 TEETH
Max torque 35 Nm

When assembled with SAE AA flange (S20 code)
the shaft dimensions must be reduced by 0.1378 In. (3.5 mm)

EG1 液压齿轮泵

EG1 Hydraulic Gear Pumps

Port Dimension

EUROPEAN STANDARD				
Size	Code	D	F	M
09-21	EE4	26 (1.023)	10 (0.393)	M5
25-99	EE6	30 (1.181)	13 (0.512)	M6

GERMAN UNIFICATION	
Size	Code
09-99	TT4


BSPP THREADS	
Size	Code
09-99	GG4

SAE THREADS		
Size	Code	D
09-21	UU4	9/16"-18 UNF
25-99	UU6	3/4"-16 UNF

NEUTRAL BODY (WITHOUT CONNECTIONS)	
Size	Code
09-99	000

Inlet Port

Outlet Port



EG2 液压齿轮泵
EG2 Hydraulic Gear Pumps


型号说明 Model Code

①	EG2	CODE										
②	A	FLANGE AND COVER	A	Aluminium								
			G	Cast iron (Heavy duty)								
③	04	DISPLACEMENT	04	06	08	11	14	17	20	23	26	
			4.2	6.2	8.3	11.1	14.2	16.7	19.6	22.7	26.1	
④	STO	FLANGE	STO			S20/S21			B80		BZ0/BN0	EZ1/EN1
⑤	T80	SHAFT	T80 M50 D92			M50 P60 S90			T50 D90		T50 D90	E80
⑥	EEX	CONNECTION	EEx TTx GGx UUx									
⑦	D	ROTATION	D	Clockwise rotation								
			S	Anticlockwise rotation								
⑧	0	STANDARD COVER	0	Standard								
⑨	0	SEALS	0	Nbr seals								
			V	Viton® seals								

性能参数 Specification

Size	Displacement (in³/rev)	Max speed rpm	Max flow (gpm)	Min speed rpm	Min flow (gpm)	Min Volum. Effic.* %
EG2-04	4.2 (0.27)	4000	16.8 (4.44)	500	2.1 (0.55)	93
EG2-06	6.2 (0.38)	4000	24.8 (6.55)	500	3.1 (0.82)	94
EG2-08	8.3 (0.51)	3500	29.0 (7.66)	500	4.2 (1.1)	95
EG2-11	11.1 (0.68)	3500	38.9 (10.28)	500	5.6 (1.48)	95
EG2-14	14.2 (0.87)	3500	49.6 (13.10)	500	7.1 (1.88)	95
EG2-17	16.7 (1.02)	3500	58.5 (15.45)	500	8.4 (2.22)	95
EG2-20	19.6 (1.20)	3300	64.7 (17.09)	500	9.8 (2.59)	95
EG2-23	22.7 (1.39)	2800	63.6 (16.8)	500	11.4 (3.01)	95
EG2-26	26.1 (1.59)	2500	65.2 (17.22)	500	13.0 (3.43)	95


* Volumetric efficiency at 1500 rpm



EG2 液压齿轮泵


EG2 Hydraulic Gear Pumps

Standard Flange ST0



Size		EG2-04	EG2-06	EG2-08	EG2-11	EG2-14	EG2-17	EG2-20	EG2-23	EG2-26
Dimension	A mm(in)	43.9 (1.73)	45.5 (1.79)	47.3 (1.86)	49.6 (1.95)	52.2 (2.06)	54.3 (2.14)	56.7 (2.32)	59.3 (2.34)	62.1 (2.45)
	B mm(in)	92.6 (3.65)	95.9 (3.78)	99.4 (3.91)	104.1 (4.10)	109.2 (4.30)	113.4 (4.47)	118.2 (4.65)	123.4 (4.86)	129.0 (5.08)
Weight(kg)		2.16	2.25	2.27	2.46	2.6	2.72	2.85	2.99	3.15

SAE A S20/SAE A-OR S21 Flange




Size		EG2-04	EG2-06	EG2-08	EG2-11	EG2-14	EG2-17	EG2-20	EG2-23	EG2-26
Dimension	A mm(in)	43.9 (1.73)	45.5 (1.79)	47.3 (1.86)	49.6 (1.95)	52.2 (2.06)	54.3 (2.14)	56.7 (2.32)	59.3 (2.34)	62.1 (2.45)
	B mm(in)	92.6 (3.65)	95.9 (3.78)	99.4 (3.91)	104.1 (4.10)	109.2 (4.30)	113.4 (4.47)	118.2 (4.65)	123.4 (4.86)	129.0 (5.08)
Weight(kg)		2.18	2.26	2.36	2.48	2.62	2.73	2.87	3.01	3.16

EG2 液压齿轮泵


EG2 Hydraulic Gear Pumps

B80 C Flange B80



Size		EG2-04	EG2-06	EG2-08	EG2-11	EG2-14	EG2-17	EG2-20	EG2-23	EG2-26
Dimension	A	45.9	47.5	49.3	51.6	54.2	56.3	58.7	61.3	64.1
	mm(in)	(1.81)	(1.87)	(1.94)	(2.03)	(2.13)	(2.22)	(2.31)	(2.41)	(2.52)
Dimension	B	94.6	97.9	101.4	106.1	111.2	115.4	120.2	125.4	131.0
	mm(in)	(3.72)	(3.85)	(3.99)	(4.18)	(4.38)	(4.54)	(4.73)	(4.94)	(5.16)
Weight(kg)		2.23	2.31	2.41	2.52	2.66	2.79	2.92	3.07	3.21

B50 C Flange BZ0/BN0




Size		EG2-04	EG2-06	EG2-08	EG2-11	EG2-14	EG2-17	EG2-20	EG2-23	EG2-26
Dimension	A	43.9	45.5	47.3	49.6	52.2	54.3	56.7	59.3	62.1
	mm(in)	(1.73)	(1.79)	(1.86)	(1.95)	(2.06)	(2.14)	(2.32)	(2.34)	(2.45)
	B	92.6	95.9	99.4	104.1	109.2	113.4	118.2	123.4	129.0
	mm(in)	(3.65)	(3.78)	(3.91)	(4.10)	(4.30)	(4.47)	(4.65)	(4.86)	(5.08)
Dimension	L	83.5	86.8	90.3	95.0	100.1	104.3	109.1	114.3	119.9
	mm(in)	(3.29)	(3.42)	(3.56)	(3.74)	(3.94)	(4.106)	(4.30)	(4.50)	(4.72)
Weight(kg)		2	2.09	2.18	2.3	2.43	2.54	2.67	2.8	2.95

EG2 液压齿轮泵

EG2 Hydraulic Gear Pumps

E50 C Flange EZ1/EN1




Size		EG2-04	EG2-06	EG2-08	EG2-11	EG2-14	EG2-17	EG2-20	EG2-23	EG2-26
Dimension	A	43.9	45.5	47.3	49.6	52.2	54.3	56.7	59.3	62.1
	mm(in)	(1.73)	(1.79)	(1.86)	(1.95)	(2.06)	(2.14)	(2.32)	(2.34)	(2.45)
	B	92.6	95.9	99.4	104.1	109.2	113.4	118.2	123.4	129.0
	mm(in)	(3.65)	(3.78)	(3.91)	(4.10)	(4.30)	(4.47)	(4.65)	(4.86)	(5.08)
	L	83.5	86.8	90.3	95.0	100.1	104.3	109.1	114.3	119.9
	mm(in)	(3.29)	(3.42)	(3.56)	(3.74)	(3.94)	(4.106)	(4.30)	(4.50)	(4.72)
Weight(kg)		1.91	1.99	2.08	2.2	2.33	2.44	2.57	2.71	2.85

EG2 液压齿轮泵

EG2 Hydraulic Gear Pumps


Shafts

T80




TAPER 1:8
Max torque 135 Nm

T50




TAPER 1:5
Max torque 140 Nm

D90




DIN Z9 GERMAN FLANGE
Max torque 110 Nm

M50




CYLINDRICAL
Max torque 90 Nm

D92




DIN Z9 STANDARD FLANGE
Max torque 110 Nm

E80




TANG DRIVE FOR ELECTRIC MOTOR
Max torque 70 Nm

P60



SAE CYLINDRICAL
Max torque 85 Nm

S90



SAE SPLINED 9 TEETH
Max torque 85 Nm

When assembled with B80 C flange (B80 code) the shaft dimensions must be reduced by 0.079 In. (2 mm)

EG2 液压齿轮泵

EG2 Hydraulic Gear Pumps

Port Dimension

EUROPEAN STANDARD

Size	Code	D	F	M	e
04-08	EE4	30 (1.18)	13 (0.51)	M6	13 (0.51)
11-26	EE5	40 (1.58)	19 (0.75)	M8	15 (0.59)

EUROPEAN STANDARD FOR MOTORS

Size	Code
04-08	/
11-26	EE6

GERMAN UNIFICATION

Size	Code	D	F
04-08	TT4	35 (1.38)	15 (0.59)
11-26	TT5	40 (1.58)	20 (0.79)






BSPP THREADS

Size	Code	BSPP
04-08	GG4	1/2" BSPP
11-26	GG5	3/4" BSPP






FILETTATURE SAE - SAE THREADS

Size	Code	U
04-08	UU4	7/8"-14 UNF
11-26	UU6	1-1/16"-12 UNF

Inlet Port



Outlet Port



EG3 液压齿轮泵
EG3 Hydraulic Gear Pumps


型号说明 Model Code

①	EG3	CODE	
②	A	FLANGE AND COVER	A Aluminium G Cast iron (Heavy duty)
③	19	DISPLACEMENT	19 22 28 33 37 44 52 61 19.05 22.2 28.3 33.2 37.2 43.98 51.9 61.4
④	ST0	FLANGE	ST0 S20/S21
⑤	T80	SHAFT	T80 S30 P20
⑥	EE5	CONNECTION	EE5 TT5 GG5 UU5
⑦	D	ROTATION	D Clockwise rotation S Anticlockwise rotation
⑧	0	STANDARD COVER	0 Standard
⑨	0	SEALS	0 Nbr seals V Viton® seals

性能参数 Specification

Size	Displacement (in ³ /rev)	Max speed rpm	Max flow (gpm)	Min speed rpm	Min flow (gpm)	Min Volum. Effic.* %
EG3-19	19.05 (1.22)	3500	66.7 (17.6)	700	13.3 (3.51)	95
EG3-22	22.2 (1.42)	3500	77.8 (20.5)	700	15.6 (4.12)	95
EG3-28	28.3 (1.82)	3300	93.5 (24.7)	700	19.8 (5.23)	95
EG3-33	33.2 (2.13)	3300	109.4 (28.9)	700	23.2 (6.12)	95
EG3-37	37.2 (2.38)	3300	122.6 (32.4)	700	26.0 (6.86)	95
EG3-44	43.98 (2.82)	3000	131.9 (34.8)	700	30.8 (8.13)	95
EG3-52	51.9 (3.33)	3000	155.6 (41.1)	700	36.3 (9.58)	95
EG3-61	61.4 (3.94)	2500	153.5 (40.5)	700	43.0 (11.35)	95

* Volumetric efficiency at 1500 rpm



ST0
Standard flange




S20 / S21
Sae A / SAE A-OR flange

EG3 液压齿轮泵


EG3 Hydraulic Gear Pumps

Standard Flange ST0



Size		EG3-19	EG3-22	EG3-28	EG3-33	EG3-37	EG3-44	EG3-52	EG3-61
Dimension	A	62.95	64.3	66.9	68.9	70.6	73.6	76.9	81
	mm(in)	(2.48)	(2.53)	(2.63)	(2.71)	(2.78)	(2.90)	(3.03)	(3.19)
Dimension	B	130.9	133.6	138.8	142.9	146.3	152.1	158.8	166.9
	mm(in)	(5.15)	(5.26)	(5.46)	(5.63)	(5.76)	(5.99)	(6.25)	(6.57)
Weight(kg)		4.98	5.1	5.34	5.52	5.68	5.93	6.24	6.6

SAE B S20/SAE B -OR S21 Flange



Size		EG3-19	EG3-22	EG3-28	EG3-33	EG3-37	EG3-44	EG3-52	EG3-61
Dimension	A	60.2	61.5	64.1	66.2	67.9	70.8	74.1	78.2
	mm(in)	(2.37)	(2.42)	(2.52)	(2.60)	(2.67)	(2.79)	(2.92)	(3.08)
Dimension	B	128	130.8	136	140.1	143.5	149.3	156	164.1
	mm(in)	(5.04)	(5.15)	(5.35)	(5.52)	(5.65)	(5.88)	(6.14)	(6.46)
Weight(kg)		4.98	5.1	5.34	5.52	5.68	5.93	6.24	6.6

EG3 液压齿轮泵

EG3 Hydraulic Gear Pumps

Port Dimension

EUROPEAN STANDARD

Size	Code
19 - 61	EE5

GERMAN UNIFICATION

Size	Code
19 - 61	TT5

BSPP THREADS


Size	Code
19 - 61	GG5

SAE THREADS


Size	Code
19 - 61	UU5

Shafts


T80







S30



P20



Inlet Port



Outlet Port

